



Built for *Business*

High-Speed, Robust A3 Scanner for Businesses

Engineered for high-volume mixed batch scanning, the imageFORMULA DR-M1060II simplifies your business' document digitisation processes. Featuring full-front operation with the U-turn path mode, you can confidently and efficiently scan all that your business needs.

UP TO
60 PPM | 120 IPM*
FAST SCAN SPEED

*300 dpi, Greyscale, A4



SCAN UP
TO A1*

*With Folio scan,
Long Document mode

UP TO
600 DPI
SCAN OUTPUT
RESOLUTION

80
SHEET
FEEDER

Compact Space-Saving Design

The U-turn path mode enables full-front operation, while saving space when the DR-M1060II is placed on countertops or tight spaces.



Fast and High-Quality Scanning

The DR-M1060II scanner offers both fast capture speeds and impressive image quality, enabling you to increase productivity and scan with confidence.



Versatile Media Handling

The scanner can handle media of a wide-range of textures and thicknesses, making it simple and quick to set up. With just a touch of a button, you can swiftly scan paper documents, receipts, IDs, and business cards.



SPECIFICATIONS / DR-M1060II

| SCANNING | | |
|--|---|--|
| Type | Desktop Sheet-Fed Scanner | |
| Scanning Speed ¹ | Greyscale | 200 dpi: 60 ppm (Simplex) / 120 ipm (Duplex) 300 dpi: 60 ppm (Simplex) / 120 ipm (Duplex) |
| | Colour | 200 dpi: 60 ppm (Simplex) / 120 ipm (Duplex) 300 dpi: 40 ppm (Simplex) / 80 ipm (Duplex) |
| Scanning Element | Contact Image Sensor (CIS) | |
| Light Source | LED | |
| Scanning Side | Simplex / Duplex | |
| Scanning Modes | Black and White, Error Diffusion, 256-level Greyscale, Advanced Text Enhancement, Advanced Text Enhancement II, 24-bit Colour | |
| Scanning Features | Folio Scanning, Double Feed Release, 2D / Barcode | |
| Optical Resolution (Max.) | 600 dpi | |
| Output Resolution ² | 100, 150, 200, 240, 300, 400, 600 dpi | |
| MEDIA HANDLING | | |
| Document Size | Plain Paper | Width: 50.8 to 300 mm Length: 70 to 432 mm (Up to 3,000 mm long with Long Document mode) |
| | Business Card | Width: 50.8 to 55 mm Length: 85 to 91 mm |
| | Card (ISO Standard) | 54 x 86 mm |
| Document Thickness and Weight | Plain Paper | U-turn Path (Page Separation): 27 to 128 g/m ² (0.04 to 0.15 mm) U-turn Path (Non-Separation): 27 to 164 g/m ² (0.04 to 0.2 mm) Straight Path: 27 to 255 g/m ² (0.04 to 0.3 mm) |
| | Business Card | 128 to 380 g/m ² (0.15 to 0.45 mm) (Use the straight path and place vertically) |
| | Card | 0.76 mm or less, 1.4 mm or less for the embossment (Use the straight path and place vertically) |
| Auto Document Feeder Capacity ³ | 80 sheets | |
| CONNECTIVITY & SOFTWARE | | |
| Interface | Hi-Speed USB 2.0 | |
| Software | ISIS / TWAIN / WIA Drivers, CaptureOnTouch | |
| GENERAL | | |
| Power Requirements | AC 100 - 240 V (50 / 60 Hz) | |
| Power Consumption | Scanning (Max.) | 32.5 W |
| | Sleep Mode | 1.9 W |
| | With Power Switched OFF (Max.) | 0.1 W |
| Operating Environment | Temperature | 10 to 32.5°C |
| | Humidity | 20 to 80% RH |
| Dimensions (W x D x H) | When Trays Are Closed | 424 x 246 x 120 mm |
| | When Trays Are Opened | 424 x 440 x 210 mm |
| Weight (Approx.) | 6.1 kg (Without AC adapter) | |
| CONSUMABLES & ACCESSORIES | | |
| Options / Consumables | Exchange Roller Kit | |
| Accessories | Flatbed Scanner Unit 102, Flatbed Scanner Unit 201 | |

Specifications are subject to change without notice.

¹ Based on A4 landscape document size.

² Primary scan lines x secondary scan lines.

³ Size: A3 or smaller (Same type document only), Paper Weight: 70 to 100 g/m², Temperature: 15 to 27.5°C, Humidity: 25 to 75% RH, Total Thickness: 10 mm or less.



Delighting You Always

**SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.**

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522

Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.