

imageRUNNER
C1533i

Canon
Delighting You Always

Experience Vibrant Performance

Efficient • Quality • Secure



Great
Ergonomics
& Usability



Fast
Scanning for
Digitisation



In-built
Security
Management





imageRUNNER C1533i

Smooth and intuitive design concept

Advance functions made simple. The new line-up introduces dynamic interface that can be customised to suit different workflows.

With exceptional V² colour technology and intuitive user interface, the imageRUNNER C1533i is set to streamline hybrid business operations in the new normal.

Easy
mobile
connectivity

Ease
of use

33ppm
Print
Speed

Up to
2,300
sheets paper
capacity

USER-FRIENDLY 7-INCH COLOUR TOUCH PANEL

Design Appeal that is Functional

The 7-inch colour touch panel offers excellent visibility which allows better reach to the edges of the panels to maximise operating areas.

The timeline function on the right of the screen provides quick reference to the last 10 used functions, saving time and improving work efficiency.



HIGH SCANNING EFFICIENCY

Fast Duplex Scanning For Efficient Digitisation

150ipm ↗


Digitising documents is the future of workflow. In streamlining paper to digital processes, the imageRUNNER C1533i offers duplex scan of up to 150ipm. The high speed automatic scanning improves efficiency greatly in the hybrid working style with frequent home and office transitions.



360 DEGREE SECURITY

Designed to keep all your data safe

Data security is the core of all businesses, especially so in the hybrid environment where access can come from anyone, anywhere. The latest features prevents unauthorised access and information leakage, so your data is in safe hands.



PREVENTS UNAUTHORISED ACCESS

The up-to-date security features ensures both network and device protection, preventing external threats to important information stored.

DATA PROTECTION

Encrypt PDFs and set passwords when digitising hard copies, so files can be opened only upon the right authentication, preventing information leakage and tampering.

HOLDING DOCUMENTS

Confidential documents sent for printing can be placed on hold and released only upon verification at the multi-function device. This prevents unnecessary information leakage by unattended documents left at the print tray.

AUTHENTICATION FUNCTIONS PROVIDED BY



uniFLOW Online*/ Online Express

The imageRUNNER C1533i takes security a step further with uniFLOW Online software which provides authentication functions for unlimited number of users. Various settings can be implemented to control the usage of the devices and reduce scan destination errors, improving overall efficiency.

* Additional software required

SPECIFICATION

MAIN UNIT	
Machine type	A4 Color Laser Multifunctional
Core functions	Print, Copy, Scan, Send, Store and Optional Fax
Control panel	7 inch TFT LCD WVGA colour Touch panel
Memory	Standard: 2.0GB RAM
Storage	eMMC: 30GB
Interface Connection	NETWORK Standard: 1000Base-T/ 100Base-TX/ 10Base-T, Wireless LAN (IEEE 802.11 b/g/n) OTHERS Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1
Paper Supply Capacity (A4, 80gsm)	Standard: 650 sheets (550 sheets x 1 cassette and 100 sheet multi-purpose tray) Maximum: 2300 sheets (with Cassette Feeding Unit-AV1)
Paper Output Capacity (A4, 80gsm)	Standard: 200 sheets Maximum: 200 sheets
Supported Media Types	Multi-purpose Tray: Thin, Plain, Recycled, Colour, Heavy, Bond, Pre-punched, Envelope, Postcard Paper Cassette: Thin, Plain, Recycled, Colour, Heavy, Pre-punched, Bond, Labels
Supported Media Sizes	Multi-purpose tray: Standard size: A4R, A5, A5R, A6R, B5R, Envelopes [No. 10(COM 10), Monarch, ISO-C5, DL] Custom Size/ Free Size: Min.76.2 x 127.0 mm up to 216.0 x 355.6 mm Paper Cassette: Standard size: A4R, A5, A5R, A6R, B5R
Supported Media Weights	Multi-purpose tray: 60 to 216 gsm Paper Cassettes: 60 to 163 gsm Duplex: 60 to 163 gsm
Warm-Up Time	4 Seconds or Less* * Time from device power on to when key operations can be performed on the touch panel display. From Sleep Mode: 10 seconds or less 12 Seconds or Less* *Time from device power on, until copy ready (not print reservation)
Dimensions (W x D x H)	500 x 556 x 640 mm
Installation Space (W x D)	717 x 785 mm
Weight	Standard: Approx. 41.0 kg including toner
PRINT SPECIFICATIONS	
Print Speed (BW/CL)	Up to 33/ 33 ppm (A4), Up to 40/ 40 ppm (A5R), Up to 55/ 55 ppm (A5)
Print Resolution (dpi)	600 x 600
Page Description Languages	Standard: UFR II, PCL6, Optional: Adobe®PostScript®3™
Direct Print	Supported file types: RUI: PDF, EPS, TIFF/ JPEG, XPS USB Memory: PDF, TIFF/ JPEG, XPS Network Place: PDF, TIFF/ JPEG, XPS
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/ K/ S/ T ¹ (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts ² ¹ Requires optional PCL INTERNATIONAL FONT SET-A1 ² Require optional BARCODE PRT KIT-D1
Operating System	UFR II: Windows® 8.1/ 10/ Server 2012/ Server 2012 R2/ Server 2016/ Server 2019, MAC OS X (10.11 or later) PCL: Windows® 8.1/ 10/ Server 2012/ Server 2012 R2/ Server 2016/ Server 2019 PS: Windows® 8.1/ 10/ Server 2012/ Server 2012 R2/ Server 2016/ Server 2019, MAC OS X (10.11 or later) PPD: Windows® 8.1/ 10, MAC OS X (10.10 or later)
COPY SPECIFICATIONS	
Copy Speed (BW/CL)	Up to 33/ 33 ppm (A4), Up to 40/ 40 ppm (A5R), Up to 55/ 55 ppm (A5)
First-Copy-Out Time (A4, BW)	Approx. 5.9/ 6.9 seconds or less
Copy Resolution (dpi)	600 x 600
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	25% - 400% (1% Increments) Preset reduction/ enlargement: 25%, 50%, 70%, 81%, 86%, 100%, 115%, 122%, 141%, 200%, 400%

SCAN SPECIFICATIONS	
Type	Standard: Single-pass Duplexing Automatic Document Feeder
Document Feeder Paper Capacity (80 gsm)	Up to 100 sheets
Acceptable Originals And Weights	Platen: Sheet, Book Document Feeder media weight : 1-sided Scanning: 42 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided Scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)
Supported Media Sizes	Platen: max. scanning size: 216.0 x 355.6 mm Document Feeder media size: A4R, A5R, A6R, B5R Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm
Scan Speed (ipm: BW/CL, A4)	1-sided Scanning: 95/ 95 (300 dpi, send), 50/50 (600 dpi, copy) 2-sided Scanning: 150/ 145 (300 dpi, send), 50/50 (600 dpi, copy)
Scan Resolution (dpi)	Scan for Copy/ Fax: up to 600 x 600 Scan for Send: (Push, BW) up to 600 x 600, (Pull, BW) up to 600 x 600 (Push, CL) up to 300 x 300, (Pull, CL) up to 300 x 300
Pull Scan Specifications	Color Network ScanGear2. For both TWAIN and WIA Supported OS: Windows®7/ 8.1/ 10/ Server 2008/ Server 2008 R2/ Server 2012/ Server 2012 R2/ Server 2016/ Server 2019

SEND SPECIFICATIONS	
Destination	Standard: E-mail/ Internet FAX (SMTP), Super G3 FAX, SMB3.0, FTP WebDAV Optional: Super G3 FAX
Address Book	LDAP (2,000)/ Local (1,600)/ One touch (200)
Send Resolution (dpi)	Push: 100 x 100, 150 x 150, 200 x 100 (Normal), 200 x 200 (Fine), 200 x 400* (SuperFine), 300 x 300, 400 x 400* (UltraFine), 600 x 600* Pull: 75 x 75, 100 x 100, 150 x 150, 200 x 200, 300 x 300, 400 x 400*, 600 x 600* *color mode is black and white only.
Communication Protocol	File: FTP (TCP/ IP), SMB3.0 (TCP/ IP), WebDAV Email/ iFax: SMTP (send), POP3 (receive)
File Format	Standard: TIFF (MMR), JPEG*, PDF (Compact, Searchable, PDF/ A-1b, Encrypted), XPS (Compact, Searchable), PDF/ XPS (Device Signature), Office Open XML (PowerPoint, Word) Optional: PDF (Trace & Smooth), PDF/ XPS (User Signature) *Single page only

FAX SPECIFICATIONS	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/ Receiving Size	Sending: A4, A5 ¹ , A6 ¹ , B5 ¹ Receiving: A4, A5, B5 ¹ Sent as B4
FAX Memory	Up to 30,000 pages
Speed Dials	Max. 200
Group Dials/ Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes

STORE SPECIFICATIONS	
Memory Media	Standard: USB Memory

ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity)
Power source	220-240V 50/ 60Hz 3.9A
Power consumption	Maximum: Approx. 1,500 W Standby: Approx. 33.3 W ¹ Sleep mode: Approx. 1.1 W ² ¹ Reference value: measured one unit ² Sleep mode is not available in all circumstances due to certain settings.

CONSUMABLES	
Toner Yield (Estimated Yield @5% coverage)	T10 TONER BK: 13,000 pages T10 TONER C/M/Y: 10,000 pages

Other Accessories
Cassette Feeding Unit-AV1, Paper Feeder PF-D1, Copy Card Reader Attachment-J1, Copy Card Reader-F1, PCL International Font Set-A1, PCL Asian Font Set-A1, PS Printer KIT-CT1, Universal Send Trace & Smooth PDF Kit-A1, Universal Send Digital User Signature Kit-C1, Barcode Printing Kit-D1, Copy Control Interface Kit-C1, Remote Fax Kit-A1, Super G3 FAX Board-BK1, ADF Access Handle-A1



Delighting You Always

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place #14-10 Galaxis, Singapore 138522
Tel: 65-6799-8888 | Fax: 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP
