



Made to *Impress*

# Wireless Refillable Ink Tank Printer with Fax for Low-Cost Printing

Enjoy the convenience of wireless printing and high-productivity with the PIXMA G4770. This 4-in-1 printer features a 35-sheet Auto Document Feeder for batch scanning productivity.

UP TO  
**8,100\***  
COLOUR PAGES

UP TO  
**7,600\***  
MONO PAGES  
\*Economy Mode

1.35"  
(34mm)  
LCD

1.35" LCD



CONNECTIVITY

## EASY, HASSLE-FREE INK REFILL

Ink refilling is now made easy. Each ink bottle nozzle is designed to fit seamlessly only into the designated ink tank, eliminating potential mixing accidents.



## EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends the printer's lifespan even when printing in high volumes.



## AUTO DOCUMENT FEEDER

Up to 35 sheets of document originals can be loaded for batch scanning and copying, eliminating the need for repeated opening and closing of the scanner lid.



## MOBILE AND CLOUD PRINTING

Print from smartphones, tablets, laptops and cloud storage with the Canon PRINT Inkjet/SELPHY and Easy-PhotoPrint Editor apps.



IMAGING **POSSIBILITIES & BEYOND**

SPECIFICATIONS			PIXMA G4770
PRINT	Maximum Printing Resolution		4,800 (horizontal) <sup>1</sup> x 1,200 (vertical) dpi
	Print Speed <sup>2</sup>	ESAT/Simplex (Mono/Colour)	11 / 6 ipm
		FPOt Ready/Simplex (Mono/Colour)	9 / 14 sec
		Photo (4 x 6")	45 sec
SCAN <sup>3</sup>	Scanner Type		Flatbed (ADF / Platen)
	Scanning Method		Contact Image Sensor (CIS)
	Optical Resolution <sup>4</sup>		600 x 1,200 dpi
Maximum Document Size	Flatbed		A4, LTR (216 x 297 mm)
	ADF		A4, LTR, LGL
COPY	Copy Speed <sup>5</sup>	Colour	sFCOT/Simplex 23 sec
		ADF (Colour)	sESAT/Simplex 3.2 ipm 1.8 ipm
	Maximum Copies	99 pages	
Maximum Document Size		A4, LTR	
FAX	Transmission Speed <sup>6</sup>	Mono/Colour	3 sec / 1 min
	Transmission/Reception Memory <sup>7</sup>		50 pages
	PC Fax		Windows: Available, Mac: Available
	Automatic Dialing	Coded Speed Dialing (max.) Group Dialing (max.)	20 locations 19 locations
PAPER HANDLING	Maximum Input Capacity	Rear Tray	Plain Paper (64 g/m <sup>2</sup> ) Up to 100 sheets Photo Paper (4 x 6") Up to 20 sheets
		ADF	Plain Paper (64 g/m <sup>2</sup> ) A4, LTR: 35 sheets, LGL: 5 sheets
	Media Size	Rear Tray	A4, A5, A6, B5, LTR, LGL, Executive, Legal, Foolscap, F4, Oficio2, B-Oficio, M-Oficio, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 x 127 mm), Custom (width: 55 – 216 mm, length: 89 – 1,200 mm)
Media Type	Rear Tray	Plain Paper (64 – 105 g/m <sup>2</sup> ), High Resolution Paper (HR-101N), Photo Paper Plus Glossy II (PP-201, PP-208), Photo Paper Plus Semi-Gloss (SG-201), Photo Paper Pro Luster (LU-101), Matte Photo Paper (MP-101), Double-Sided Matte Paper (MP-101D), Photo Stickers (PS-208, PS-808), Envelope	
NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility		Please visit <a href="https://asia.canon">https://asia.canon</a> to confirm OS compatibility and to download the latest drivers. Windows 11 / 10 / 8.1 / 7 SP1 <sup>8</sup> macOS 10.14.16 – 12 or later Chrome OS
	Interface		Wireless LAN IEEE802.11b/g/n/a <sup>9</sup> /ac <sup>9</sup> USB 2.0
	Canon Printing Apps	Mobile Others	Canon PRINT, Easy-PhotoPrint Editor, Creative Park Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect
	Mobile/Cloud Printing Solutions		AirPrint, Mopria, Canon Print Service (Android), Direct Wireless, Cloud Service
	Power		AC 100 – 240 V, 50/60 Hz
	Power Consumption <sup>10</sup>		15 W (Standby: 0.6 W)
	Duty Cycle		Up to 3,000 pages/month
	Recommended Monthly Print Volume		150 – 1,500 pages
	Operation Panel	Display	1.35" / 3.4 cm LCD (Monochrome)
	Dimensions (W x D x H)	Factory Configuration	
Output/ADF Trays Extended		416 x 556 x 268 mm	
Weight		7.2 kg	
CONSUMABLES	Ink Bottles	Type/Colours	Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow
		Page Yield <sup>11</sup>	Plain Paper
	Photo Paper (PP-201)		GI-71S PGBK: 3,100 (Economy Mode <sup>13</sup> : 3,900) GI-71S C, M, Y: 4,400 (Economy Mode <sup>13</sup> : 4,600)
	User Replaceable Maintenance Cartridge		4 x 6" Photos <sup>14</sup> : GI-71 PGBK: NA / GI-71 C, M, Y: 2,200 GI-71S PGBK: NA / GI-71S C, M, Y: 1,200
			MC-G04

**Specifications are subject to change without notice.**

- <sup>1</sup> Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- <sup>2</sup> Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- <sup>3</sup> TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- <sup>4</sup> Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available only when you use TWAIN Driver.
- <sup>5</sup> Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.
- <sup>6</sup> Black & white document fax transmission speed is based on default setting using ITU-T No. 1 chart. Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- <sup>7</sup> Page count is based on ITU-T No1 chart or Canon FAX Standard Chart No. 1.
- <sup>8</sup> Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.
- <sup>9</sup> Wireless LAN IEEE802.11a/ac are available for Taiwan models only.
- <sup>10</sup> When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- <sup>11</sup> Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.
- <sup>12</sup> Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the replacement ink bottles after initial setup. The colour yield is based on 1 set of composite colour bottles.
- <sup>13</sup> The Economy mode reduces the ink consumption by lowering the density. More pages can be printed using this mode.
- <sup>14</sup> Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement ink bottles after initial setup. Black ink is not used when printing under this condition. However, a minimal amount of black ink is used for maintenance purposes.



Delighting You Always

**SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS  
CANON SINGAPORE PTE. LTD.**

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522  
Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

**DEALER'S STAMP**

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.