

varioPRINT 140 series QUARTZ

BUILT FOR BUSINESS: CLASS LEADING PRODUCTION PRINTER – SUPERB UPTIME AND OUTSTANDING IMAGE QUALITY

The Canon varioPRINT 140 series QUARTZ offers unparalleled reliability, impressive quality, green credentials and excellent output speeds, setting a new standard for monochrome production printing.



- Consistently high-quality prints thanks to DirectPress technology
- Speeds of up to 143 images per minute
- Maximum output volume of 800,000 images per month
- Peerless reliability means the printer requires minimal maintenance
- EnergyLogic delivers truly sustainable printing with zero ozone emissions
- HeatXchange technology further reduces energy consumption
- Embedded PRISMAsync controller offers intuitive operation and simplified scheduling
- Seamless workflow integration for smooth end-to-end production
- Range of inline accessories and DFD support for online finishing
- Superb registration, with excellent line-sharpness and halftone uniformity

Canon

TECHNICAL SPECIFICATIONS

varioPRINT 140 series QUARTZ

TECHNOLOGY

Description	Black & white printer / scanner / copier		
Imaging technology	Océ DirectPress®		
Toner	Mono-component toner		
Engine resolution	600 x 2400 dpi		
Features	Toner Transfer Fusing (TTF) technology, HeatXchange technology, On-the-fly toner and paper refill; Automatic duplexing (up to 300 gsm), Active registration		
Options	Operator attention light with adjustable warn-ahead functions, CCD interface		
Print speed (simplex and duplex)	A4 duplex	A3 duplex	SRA3 duplex
varioPRINT 140	143 ipm	75 ipm	70 ipm
varioPRINT 130	133 ipm	69 ipm	65 ipm
varioPRINT 115	117 ipm	61 ipm	58 ipm

SEGMENT

Recommended monthly print volume (A4)	varioPRINT 140: 200,000-800,000
	varioPRINT 130: 150,000-650,000
	varioPRINT 115: 80,000-500,000
Maximum monthly print volume (A4)	varioPRINT 140: 2,200,000
	varioPRINT 130: 2,000,000
	varioPRINT 115: 1,700,000

GENERAL

User operation	Integrated 15" full colour touchscreen operator panel; Full engine / controller integration with one point of control PRISMAsync controller Remote Control: iOS/Android application Remote monitoring: on desktop via Remote User Interface Remote Meter Reading: secure and easy transmission of meter readings Remote Diagnostics: for maximum printer uptime Remote Software Upgrade: always the latest software and functionality available
Warm-up time	150-270 seconds, depending on amount of toner in cleaner
First copy time	Simplex: 3.9 seconds
First print time	Simplex and ripped: 5.1 seconds
Registration tolerance	Maximum +/- 0.5 mm (A4 images)
Dimensions main engine (WxDxH)	1130 x 765 x 1040 mm (excluding user interface) 1130 x 765 x 1430 mm (including user interface)
Weight main engine	263 kg (with Scanner / Automatic document feeder)
Certificates	EPA Energy Star® / TEC compliance, RoHS, Cetecom / CE Class A, FCC Class A, UL / TÜV / CE, REACH
Product Safety & Environment	EPA/TEC compliance, RoHS compliance, Cetecom / CE Class A, FCC Class A, UL / TÜV / CE, VCCI, ErP, China RoHS, CRDH FDA (USA), WEEE, Green Procurement Standards, EAC, KC, RCM, International Energy Star
Other compliances	Section 508, EPEAT BRONZE, De-inkability certificate
Operating system	Windows 10
Processor	3.1 GHz
Memory	4 GB
Hard disk	500 GB
Interface	10/100/1000 Base-T
Page Description Language	APPE (Adobe® PDF Print Engine); Adobe® PostScript® 3TM/ streaming PostScript®; PPML/GA Level 1; PPML versions 1.5, 2.1 and 2.2 PDF 1.7; PCL 6; XPS; IPDS (options); Xerox® PPP support
Fonts	136 Type1 fonts for roman languages Use of PostScript fonts via Settings Editor
Protocols	TCP/IP (LPR/LPD, socket), SMB static/auto IP (via DHCP), SNMP v1-v3 (printer MIB, private MIB), Job monitoring MIB, IPP
Printer drivers	PS3 UPD - Windows Server 2003(R2) / Vista/Windows Server 2008 / Windows 7 / Windows Server 2008 R2 / Windows 8 / Windows server 2012 / Windows 8.1 / Windows 2012 R2 / Windows 10 / Windows Server 2016 PS3 PPD - legacy Windows and MAC/Linux-CUPS/other PS3 - Macintosh (Mac OS 10.6/10.7/10.8/10.9/10.10 / 10.11 / 10.12 / 10.13) PCL6 UPD - Windows Server 2003(R2) / Vista/Windows Server 2008 / Windows 7 / Windows Server 2008 R2 / Windows 8 / Windows server 2012 / Windows 8.1 / Windows 2012 R2 / Windows 10 / Windows Server 2016 PCL6 GPD - legacy Windows and MAC/Linux-CUPS/other MicroSoft XPS UPD - Microsoft Windows Client Vista / Windows Server 2008 / Windows 7 / Windows Server 2008 R2 / Windows 8 / Windows server 2012 / Windows 8.1 / Windows 2012 R2 / Windows 10 / Windows Server 2016 SAP Device Type (SAP R/3 4.6 and higher)

Security

E-shredding, HTTPs, Firewall, PIN for Doc Box, User authentication to SDS, Removable hard disk, IPv6, software protection license (integrity checker), user authentication per user role: key operator, system administrator and service representative

Features

Print while RIP, Streaming, Multi-job processing, Pre-RIP, no cycle-down between jobs, multi-tasking (scan/copy/print), web-based configuration with Settings Editor, Remote meter reading, Remote Diagnostics, Remote software upgrade, Remote Monitor

Optional licenses

DocBox, Schedule, Remote Viewer, Scan to file/e-mail, E-shredding, Multiple queues, Streaming printing, Accounting, Font sets: Korean, Japanese, Simplified Chinese, Traditional Chinese, DPLink (integration in customer Xerox infrastructure), KDKLink (integration in customer Kodak infrastructure), PRISMAlytics Dashboard

ENVIRONMENTAL

Sound power level

Ready mode: max 33dB
Print mode: max 64dB

Ozone emissions

None (engine)

Power requirement

1-Phase, 200 - 240 V; 50/60 Hz

Power consumption

Ready mode: 270W
Low power mode: 150W
Sleep mode: 4.3W (excl. controller)
Operation (duplex): vP115: 1.9 kW
vP130: 2.0 kW
vP140: 2.2 kW

Optimum temperature & Relative humidity

17° C - 30° C / 20% - 80%

Room ventilation

50 m³ or >2AC/hr at room size > 50 m³

INTERNAL PAPER MODULE

Paper trays

2 x 1500 sheets (80 gsm)
2 x 500 sheets (80 gsm)

Paper size and weight

50 - 300 gsm
A4, B5 and A5 (bulk trays 1+2)
140 x 182 mm - up to 320 x 432 mm (tray 3)
140 x 182 mm - up to 320 x 488 mm (tray 4)

Paper feed technology

Friction feed, Paper Logic from all trays

EXTERNAL PAPER MODULE-D1

Description

Optional external paper input module with single or dual paper trays

First module

2 x 1700 sheets (80 gsm, all sizes)
2 x 600 sheets (80 gsm, all sizes)
Dual configuration: max. 2 x 3400 sheets (80 gsm, A4)
2 x 600 sheets (80 gsm, all sizes)

Maximum paper capacity

8,000 sheets (A4 80 gsm) / 4,600 sheets (all sizes)

Paper size and weight

50 - 300 gsm
203 x 203 mm - 320 x 488 mm (all trays)

Paper feed technology

Suction feed, Air separation, Paper Logic from all trays

Dimensions (WxDxH)

987 x 743 x 1056 mm

Weight unit

203 kg

Power requirement

90-264 V, 40-67 Hz, 200 W

Features

Automatic paper size detection, Tray-empty detection, On-the-fly paper loading, Paper-level indication, Tab sheet processing, Custom paper size support, Optional dual paper trays

PRINTING

Job management

DocBox, Queue and History, Waiting Room

Print resolution

Adobe PostScript 3: 1200 x 1200 dpi, 600 x 2400 dpi
PCL: 600 x 600 dpi

Maximum printable area

Adobe PostScript 3: 3 mm from side, maximum 308 x 484 mm

Screen frequency

PCL: 6 mm

Grey levels

PCL: maximum 106 lpi

Features

Adobe PostScript 3: maximum 200 lpi

Features

Adobe PostScript 3: 200

Features

PCL: 125

Features

RIP at rated engine speed, Pre-RIP, Print-while-rip-while-spool (Streaming), Mixplex, Hotfolder & multiple queue support

TECHNICAL SPECIFICATIONS

varioPRINT 140 series QUARTZ

COPYING

Copy resolution	600 x 1200 dpi
Exposure control	Auto / Manual (9-step scale), Text, Text / Photo, Photo
Zoom	25 - 400%; automatic
Screen frequency	200 lpi
Grey levels	200
Features	Automatic quality optimization for text / photo

SCANNING

Resolution	75, 100, 150, 200, 300 (default), 600 dpi
Colour scanning	Optional
Destination	Scan-to-Email, Scan-to-DocBox, Scan-to-FTP, Scan-to-USB
File format	PDF (single-page and multiple-page), TIFF, JPEG / sRGB (colour scanning)
Features	Thumbnail preview (DocBox), Scan profiles, Status overview, Scan-once-print-many, Scan-while-warming up, Scan-while-print, Subset-scanning, RGB color scanning, Scan to File mixed sizes

DUPLEX COLOUR IMAGE READER Unit-N1

Capacity	200 sheets (80 gsm)
Maximum resolution	600 x 600 dpi
Maximum scan speed	A4, Black & white/colour, 300 x 300dpi: 115ipm up to 139ipm/136ipm A4, Black & white: 600 x 600dpi: up to 139ipm A4, Colour, 600 x 600dpi: up to 36ipm A3, A4, A4R, A5, A5R, Free sizes (W x L): A3, A4, A4R, A5, A5R, Free sizes (W x L): Min. 140 mm x 128 mm, Max. 432 mm x 305 mm
Auto detectable original size	A3, A4, A4R, A5, A5R, Free sizes (W x L): Min. 140 mm x 128 mm, Max. 432 mm x 305 mm
Paper weight	1-sided: 38 - 220 gsm 2-sided: 38 - 220 gsm

DOCUMENT INSERTION UNIT-N1

Number of Trays	2-bin
Tray Capacity	200 sheet / bin
Paper Weight	52 - 300 gsm
Paper Size	A3, A4, A4R, SRA3, 13"x19", Free size (182 x 182 mm to 330.2 x 487.7 mm)
Power Source / Consumption	230V 10A
Dimensions	336 mm (746 mm including Tray) x 793 mm x 1407 mm
Weight	Approx 61 kg

HIGH CAPACITY STACKER-H1

Stack Tray Capacity	Stack tray: 6,000 sheets (80 gsm) in two stacks of 3,000 sheets each
Top Tray Capacity	Top Tray: 200 sheets
Acceptable Paper Weight	50 - 300 gsm
Acceptable Paper Size	Max defined for main engine. Custom sizes between min. 140 x 182mm up to 320 x 488mm, mixed sizes, tabs and folded sheets 230V 10A (2nd Stacker can get power from 1st Stacker)
Optionals	DFD interface kits for 860 mm and 1002 mm
Dimension	899 x 745 x 1040 mm
Weight	Approx 210 kg

PAPER FOLDING UNIT-J1

Basic Information	Z Fold, C Fold, Zigzag Fold, Double Parallel
Acceptable Paper Weight	50 - 105 gsm Double parallel: 50 - 90 gsm
Acceptable Paper Size	A4R Z-fold: A3, B4
Power Source	From Finisher-W1 or booklet Finisher-W1
Dimension	336 x 793 x 1190 mm
Weight	Approx 71 kg

FINISHER-W1/AG1

Basic Information	Staple and stacking finisher
Number of Trays	2
Upper Tray (A) Capacity	A4/A4R/A5R 1,000 sheets, A3 1,000 sheets, SRA3/13"x19" 1,000 sheets
Lower Tray (B) Capacity	A4 4,000 sheets, A4R 2,000 sheets, A3 1,500 sheets, SRA3 1,000 sheets
Stapled stacking capacity	A4 200 sets or max 3,000 sheet
Stapling Position	Corner, Double
Acceptable Paper Weight	50 - 300 gsm
Staple Capacity:	A4: 100 sheets, A3/A4R: 50 sheets
Power Source	230V x 10A
Dimension	800 x 792 x 1239 mm
Weight	130 kg

BOOKLET FINISHER-W1 /AG1

Basic Information	Same functionality as Finisher W1/AG1 and additional saddle stitching and V-folding functionality Up to 100 pages booklet available (2 - 25 sheets) Stack capacity up to 5000 sheets and up to 100 sheets stapled
Number of Trays	2
Upper Tray (A) Capacity	1,000 sheets A4/A4R/A5R, 1,000 sheets A3, 1,000 sheets SRA3/13"x19"
Lower Tray (B) Capacity	A4 4,000 sheets, A4R 2,000 sheets, A3 1,500 sheets, SRA3 1,000 sheets
Stapled stacking capacity	A4 200 sets or max 3,000 sheet
Stapling Position	Corner, Double
Acceptable Paper Weight	50 - 300 gsm
Booklet stitch paper size	A3, A4R, SRA3, 13"x19", Free size 210 x 279.4 mm to 330.2 x 487.7 mm
V-Folding	Up to 5 sheets
Power Source	230V x 10A
Dimension	800 x 792 x 1239 mm
Weight	Approx 180 kg

BOOKLET TRIMMER-F1

One Edge Trimming	Fore-edge
Trim Width	2 - 28 mm
Trim Thickness	Up to 50 sheets (includes Cover, by half fold)
Acceptable Paper Weight	50 - 300 gsm
Output Tray Capacity	30 booklets
Power Source	Booklet finisher W1
Dimension	2,095 mm (including joint, conveyer and output tray: 162 mm) x 790 mm x 1,040 mm
Weight	Approx 152 kg

TWO-KNIFE BOOKLET TRIMMER-A1

Basic Information	Top and Bottom Edge trim
Trim Width	2 - 15 mm
Trim Thickness	Up to 50 sheets (includes Cover, by half fold)
Acceptable Paper Weight	50 - 300 gsm
Output Tray Capacity	30 booklets
Power Source	230V x 10A
Dimension	536 x 770 x 1040 mm
Weight	Approx 145 kg

TECHNICAL SPECIFICATIONS

varioPRINT 140 series QUARTZ

PUNCH UNIT BT1 / BU1

Basic information

Requires either the Booklet Finisher W1 or Staple Finisher W1

Punch Hole type

BT1: 2 holes and 4 holes (FRN) selectable, BU1: 4 holes (Swe)

Acceptable Punch Paper Weight:

52 - 300 gsm

Acceptable Punch Paper Size:

2 holes: A3, A4, A4R, Free size (182 x 182 to 297 x 432.0 mm)
4 holes: A3, A4, Free size (257 x 182 mm to 297 x 432 mm)

Weight:

Approx 7.7 kg

MULTIFUNCTIONAL PRO PUNCHER-B1

Basic information

External In-line Punch Unit

Acceptable Paper Weight:

75 - 300 gsm (Plain paper), 118 - 300 gsm (Coated paper), 157 - 300 gsm (Crease/ Plain & Coated paper)

Acceptable Paper Size

Punch: A4, A4R, SRA4, A3, SRA3

Crease: A4R, A3, SRA3, 13 x 19

Punch tools

Plastic Comb 21-Hole, Twin Loop 23-Hole (Round/Rectangle), Twin Loop 34-Hole (Round/Square), Color Coil 47-Hole, Velo Bind 12-Hole, Loose Leaf 4-Hole Punch, Loose Leaf 2-Hole Punch, Loose Leaf 4-Hole (Swedish), Loose Leaf 3-Hole, Crease

Power source

230V x 2A

Dimensions

445 mm x 795 mm x 1040 mm

Weight

Approx 102 kg

DFD ADAPTER-A1

Basic information

Enables DFD connectivity directly beside the engine

Acceptable paper weight

Same as engine

Acceptable paper weight

Same as engine

Optionals

DFD Interface kit for 1002 mm. Standard DFD height is 860 mm.

Power source

230 V x 10 A

Dimensions

300 mm x 745 mm x 1040 mm

Weight

Approx 60 kg

FINISHER BRIDGE-A1

Basic information

Offers connectivity of Finisher-W1 and Booklet Finisher-W1 with 3rd party DFD finishing equipment. Always in combination with DFD Adapter-A1

Acceptable paper weight

Same as engine

Acceptable paper weight

Same as engine

Power source

Power and control from DFD Adapter-A1

Dimensions

600 mm x 745 mm x 150 mm

Weight

Approx 30 kg

OUTPUT TRAY

Basic information

Basic tray face-up / face-down stacking

Paper Size:

All available size on marking engine

Paper Weight

50 to 300 gsm

Output Capacity

250 sheets at simplex printing/100 sheets at duplex printing

Dimensions

360 mm x 547 mm x 256 mm

Weight

Approx. 4.2 kg

3RD PARTY FINISHER

Basic information

The varioPRINT 140 series can be configured also with 3rd party finishing. Please find here a list of listed and approved finishers

Plockmatic Pro 50 and Pro 35 Booklet makers

BLM300 Booklet maker

BLM600 Booklet maker

Max Ring binding finisher MB-1000C

GBC eWire Pro

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD. 1 Fusionopolis Place Galaxis #14-10 Singapore 138522

Tel: +65-6799 8888

Fax: +65-6799 8882

www.canon-asia.com

www.canon.com.sg



This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.